

Troubleshooting

Water appearance

WHITE water. When a new water filter or cartridge is installed or after cleaning, the water may appear milky or white for a while. It is harmless and will soon clear. White water is due to micro bubbles of air. On standing, the water will become clear as the bubbles move upwards. Water in some areas of the country has a high level of lime or calcium. The redox inside the unit changes these substances into harmless elements which react with air and temperature.

BLACK water. When a new water filter or cartridge is installed or after cleaning, very fine black particles may appear in the water. This is normal and the particles are harmless carbon. Flushing the system for a few minutes by turning the tap on and off rapidly several times will help to clear this.

COLORED water (often RED). Water in some areas may be high in dissolved iron and this can pass through the filter. When the water is left to stand, dissolved iron gives a red or brown color as the iron oxidizes (rusts). In very severe cases you should contact Crystal Quest® for specialist advice. Ordinary particulate rust in the water will be removed by the system.

Water taste

Filtered and treated water tastes so much better than unfiltered water. But there are also some who cannot detect any change. Others find that the treated water tastes "different", but they will soon become accustomed to the taste of the filtered water. A major factor affecting taste may be the natural composition in a particular area. There can be considerable local differences in the mineral content of the water, for example.

Fish odor and sour taste water. System is not flushed properly. Run the water for five minutes and shut off for five minutes. Do three to four times consecutively. Some areas might have hard water. In very severe cases you should contact Crystal Quest® for specialist advice.

Chlorine taste. The "natural" taste of an area's water is often masked by the presence of chlorine used in the treatment process. If the chlorine taste consistently reappears, the cartridge should be replaced. If after prolonged standing or during infrequent use any strong objectionable taste occurs, flush the system by running water for 5 minutes.

Bad taste and/or odor. The cartridge needs replacing.

Water Leaks

Your system has been tested before leaving the factory. In the unlikely event of a fault, small leaks sometimes do occur as a result of incorrect assembly or abuse. The following tips may be helpful:

- Depending on the positioning of the filter and the temperature of the incoming water and air, condensation on the outside of the filter housing may occur, resulting in a frosted appearance of fine water droplets on the surface. This does not, of course, mean that there is a leak in the system. The remedy is to either insulate the area around the filter or reposition it.
- Leaks can occur if cartridge is not installed properly. Cartridge must be installed according to the directional arrow on the cartridge which indicates "This End Towards Cap".
- Always ensure that sump top is snapped into sump by being pushed in.
- Always ensure that the sump ring is screwed fully onto the sump top. This is essential both for the internal seal and the housing seal. Use Teflon tape around sump if necessary.
- In the event of a leak, carefully examine its source. Water from a leak may run along the pipe work. (It may drip or collect some distance from the actual location of the leak.)
- Leaks occurring at the line saddle valve may mean that the unit has not been fully clamped onto the water line. (Adhere to the instructions given on page 3.)
- Leaks at the quick fittings are usually due to the tubing not being pushed fully into the fitting. Remove the tubing, cut off an inch of tubing with a sharp knife and reinsert into the quick fitting. Ensure that the quick fit collet is in position. When fitted correctly, the tube should not pull out of the fitting (unless the collet is pushed in at the same time to release the tubing).
- If there are leaks at the compression fittings, make sure that the components are fitted correctly and that the compression nuts are fully tightened.
- If there is a leak from the body of the faucet, check that the tap outlet arm is pushed down firmly. Two O-rings are fitted to the faucet outlet spout; ensure they are still in position.
- If there is a leak from the water filter inlet and outlet, unscrew fitting, wrap Teflon® tape around it, and screw it back.

To eliminate possible water and property damage, use the following preventative steps and devices:

- A licensed plumber should install this unit, reading and following the Installation and Operation Guide as well as all notices.
- Install a water pressure regulator/control valve inline to keep the water inflow pressure at 60 psi or less.
- Keep the water supply line from extreme heat or freezing. Temperature at unit location should be maintained between 35° F and 120° F.
- Install an auto shut-off/leak detector (Fig 7) for undersink water filter applications. Leak controllers are specialized water shut-off systems that use sensors to detect a water leak. The sensor sounds an alarm and then shuts off the water. The alarm continues to sound until the valve is manually reset.
- In addition to having all other safety devices, use the T-valve or saddle-valve handle to shut off the inflow of water to the system during vacation.
- To avoid premature clogging and properly maintain cartridge(s), rinse regularly or replace cartridge(s).
- The use of a 3-way faucet will help avoid pressure buildup where water is turned off at filter faucet.

Online warranty registration

<http://crystalquest.com/warranty.htm>



To order replacement cartridges

<http://crystalquest.com/water-filter-replacement-cartridge.htm>

No water


- Check that the water filter faucet is open and that the main water is still on.
- Check that the saddle valve (or T-valve if used) is open.
- Check that all the tubes are connected correctly.
- Check direction of water flow.

Low water flow

- Check that you have removed all the shrink wrap from new filter cartridge.
- During periods of high water demand the pressure may fall as will the water flow from the filter. Running a bath, shower or appliance connected to the same line on which your system is connected may starve the unit of water.
- Reduction of water flow sooner than normal may be an indication of a high volume of sediment in your water. Add sediment pre-filter, backwash the system, and/or replace the cartridge.
- Check that the saddle valve (or T-valve) is fully opened or if there is low flow at the time of installation, check that the saddle valve (or T-valve) instructions were carried out correctly and that the water line has been pierced fully. Close the line valve fully and then open it again.
- The filter system needs a minimum pressure of 20 psi to work. If the pressure is inadequate a pump may be needed, and for this you should contact Crystal Quest® or a plumber.

High water flow

- If the water flow has excessive force, this will lead not only to splashing at the tap but also to lower performance from the filter. Reduce the flow rate to the minimum acceptable by turning the line saddle valve handle clockwise. For optimum performance, a flow rate of 0.5 gpm is suggested.



- CQE-RC-04000 5-Micron Carbon Block Filter Cartridge
- CQE-RC-04001 5-Micron Sediment Reusable Pleated Filter Cartridge
- CQE-RC-04002 2-7/8" x 9-3/4" Multistage PLUS Filter Cartridge
- CQE-RC-04055 2-7/8" x 9-3/4" UF Membrane Filter Cartridge
- CQE-RC-04005 2-7/8" x 9-3/4" Ceramic
- CQE-RC-04006 2-7/8" x 9-3/4" Fluoride Filter Cartridge
- CQE-RC-04049 2-7/8" x 9-3/4" Fluoride/Multistage Filter Cartridge
- CQE-RC-04007 2-7/8" x 9-3/4" Nitrate Filter Cartridge
- CQE-RC-04050 2-7/8" x 9-3/4" Nitrate/Multistage Filter Cartridge
- CQE-RC-04008 2-7/8" x 9-3/4" Arsenic Filter Cartridge
- CQE-RC-04051 2-7/8" x 9-3/4" Arsenic/Multistage Filter Cartridge



WaterSimplyPure.com Installation and Operation Guide

Mega 1000

Mega 2000

Mega 3000


Operating Specifications

Pressure Range:	30-60 psi (2.1-4.2 bar)
Temperature Range:	40-90°F (4.4-32.2°C)
Rated Service Flow:	0.3-0.5 gpm

Important!

- All equipment needs to be plumbed into the water system by a qualified, licensed plumber. Check with your local public works department for plumbing codes.
- Crystal Quest® accepts no liability for property damage.
- Use this system on a potable (safe-to-drink) COLD water supply only.
- It is recommended that a pressure regulator/control valve be installed inline before the system to keep the water inflow pressure at 60 psi or less. This will reduce the water pressure flow to the system and will prevent water pressure spikes, water hammering, and excessive water pressure buildup. Alternatively, if a pressure regulator/control valve is not used, the use of a 3-way faucet will help avoid pressure buildup where water is turned off at filter faucet.
- Installation must comply with local, state, and federal plumbing codes and health department rules and regulations. These guidelines must be followed while installing the system.
- Install an inline flood prevention valve/leak detector controller to avoid accidental property damage and make the system failure-proof (available on the market or at www.crystalquest.com).
- O-rings should be properly seated in the groove of the sump, or water leaks could occur.
- Make sure locking clips (blue clip) are secured to the outlet/inlet fittings after tubing is inserted.
- Keep the water supply line from extreme heat or freezing. Temperature at unit location should be maintained between 35° F and 120° F.

CRYSTAL QUEST® Mega Undersink Water Filter





Mega 1000
6-Stage Filtration
CQE-US-00303
CQE-US-00304
CQE-US-00305

Mega 2000
7-Stage Filtration
CQE-US-00306
CQE-US-00307
CQE-US-00308

Mega 3000
8-Stage Filtration
CQE-US-00309
CQE-US-00310
CQE-US-00311

All drawings, pictures, colors, and sizes are approximate for illustration purposes only and may not reflect the end product. All models are subject to change without notice.

Preparing for Installation

Read the instructions carefully and learn the specific details regarding installation and use. Failure to follow them could cause serious property damage.

- Inspect the carton and unit for evidence of rough handling and concealed damages. If contents appear damaged, ask driver or contact carrier for a damage claim form to fill out. Shipper must be notified immediately. Remove components from shipping carton. Check that all installation parts are present, which includes the unit, faucet, installation hardware and tubing. If any part is missing or damaged, do not attempt to install the filter. Please contact customer support for replacement parts at (800) 934-0051.


Tools and Material Recommended for Installation

- Safety glasses
- 3/8" variable speed electric drill, 1/8" and 1/2" bits
- 1-1/4" porcelain hole cutter (if hole for second faucet is not provided)
- Extension cord, drop light or flashlight
- Plastic anchors and screws
- Plastic tube cutter
- Air pressure gauge (low pressure)
- Pliers
- Phillips head and flat head screwdrivers
- 1-1/4" wood bit
- Household bleach (liquid)
- Adjustable wrench
- Crescent wrench
- Teflon® tape
- Air pump (hand)

Easy To Install

STEP 1 – Install the Faucet (Fig 1)

Faucet should be placed near the sink where drinking/cooking water is normally required. **A 2" flat surface is required to mount the faucet** if an existing hole for a second faucet is not available. The mounting thickness should not exceed 1-1/4". If the sink has a sprayer, it may be disconnected for faucet installation. A pipe cap or plug will be necessary to seal the sprayer connection. If making the faucet mounting hole (if sprayer or second hole is not used), check to make sure the drill does not interfere with anything below. Center punch a small indent at the desired faucet location (2" flat surface is required, not exceeding 1-1/4" in thickness). Drill the required pilot hole of the chassis punch and tighten nut to cut the desired hole size. Clean up sharp edges. The faucet should be positioned so it empties into the sink and the spout swivels freely for convenience. If sink has a hole that can accommodate the faucet, no drilling is required. Proceed with mounting the faucet.



Mounting the Faucet:

Disassemble hardware from the threaded nipple, except for chrome base plates and rubber washers. (Rubber washers may be replaced with a bead of plumber's putty for neater appearance.) Feed the threaded nipple through sink or counter mounting hole and position the faucet. From below sink or counter, assemble the white spacer flat washer and hex nut on threaded nipple and tighten by hand (open end up; open side toward air gap). After checking faucet orientation, tighten with a wrench until secure (Fig 1).

Important!

Do not use washable prefilter with undersink units.

STEP 2 – Install the Saddle (Feedwater) Valve and Tubing (Fig 2)

CHOOSE THE VALVE LOCATION

- Choose a location for the valve that is easily accessible. It is best to connect into the side of a vertical water pipe. When it is necessary to connect into a horizontal water pipe, make the connection to the top or side, rather than at the bottom, to avoid drawing off any sediment from the water pipe.
- Disconnect the cold water supply line. Attach and tighten the saddle valve connector assembly, being careful not to pinch or crimp any tubing or water supply line while tightening. Use Teflon® tape to ensure a tight fit.

NOTE: The saddle valve clamps onto hard tubing or pipe. It will make its own hole in copper tubing but not in iron or brass. For brass or galvanized iron pipe, drill a 1/4" hole in pipe before mounting saddle valve. If possible, use a hand or cordless drill when drilling water pipe. If using an electric drill, be sure that drill, cord and outlet are all properly grounded.

NOTE: If water supply line is soft tubing, it is recommended to use a T-valve installation.

NOTE: Do not turn handle before installing or while installing saddle valve. To prevent damage to piercing needle, make sure that piercing lance does not project beyond the rubber gasket.

NOTE: Leave handle in this position (valve closed) until filter installation is complete.

- Hold backplate against tube.
- Hold saddle valve against tubing in a position directly opposite backplate.
- Tighten screw enough so saddle valve and backplate are held securely against tube.
- Tighten screw firmly. Do not crush tube.

CONNECT SOURCE WATER FEED TUBING TO VALVE BODY USING COMPRESSION FITTING

- Slide nut and sleeve onto tubing (in that order).
- Install insert into tubing.
- Install tubing with insert and sleeve into valve body.
- Thread compression nut onto valve body. Tighten.
- Turn saddle-tapping valve handle clockwise until it is firmly seated and piercing lance is fully extended.

CAUTION: When the supply line is pierced, the valve should be closed. Do not open valve until system is activated. Turn on cold water supply. Check saddle-tapping valve installation for leaks. Allow water to run from faucet for a few minutes to clear any debris in the line caused by installation.

NOTE: If flow from sink faucet is reduced, clean faucet aerator.




Fig 2

Connecting Tubing into Filter (Figs 3, 4, and 5)

PLASTIC TUBING

- Cut tube ends square and straight. Do not deform tube (i.e., cause tube to compress its diameter so it is no longer round).
 - Avoid sharp changes in direction when routing tubing. Sharp turns cause tubing to flex and deform, which reduces its flow capacity and may increase lateral stress on the fittings, causing leakage.
- Remove red end caps from unit's water inlet/outlet connections.
 - Push in tube from saddle valve through water filter INLET fitting (Fig 3). Remove blue locking clip, if any.
 - Push in tube from faucet through water filter OUTLET fitting (Fig 3). Reattach blue locking clip, if any.




Fig 3

CONNECT USING QUICK-CONNECT FITTINGS

- Fittings consist of three parts: a body, collet, and a locking clip. Make sure outer surface of tube is clear of marks or scratches for a length equal to twice tube diameter. This allows O-ring to seat properly against tube.
- Remove locking clip from body collet (A).
- Push tube through collet into body until it seats firmly at bottom of fitting. Not replacing the locking clip may cause the tube to eject, resulting in water damage (A, B).




Fig 4A

REMOVE FITTINGS

- To remove a tube, turn off the water. Remove locking clip.
- Push and hold collet against body (ring of the connector) square against the fitting while pulling tube out.
- To reinsert a tube, cut 1/2" of tube from the end. This will help prevent leaking. Replace the locking clip around the collet.



Fig 4B

CONNECT USING COMPRESSION FITTINGS

- Slide compression nut over the end of tubing.
- Connect compression nut to compression adapter and tighten the compression nut securely.




Fig 5

Changing Filters (Fig 6)

NOTE: THIS MEGA UNDERSINK SYSTEM CONTAINS CARTRIDGES WHICH MUST BE REPLACED AT REGULAR INTERVALS TO MAINTAIN PROPER PERFORMANCE. USE ONLY FACTORY APPROVED CARTRIDGES.

Use a drip pan to catch any water that may spill when the filter housings are removed.

- Close the saddle valve that feeds the filter.
- Release any pressure in the line by turning on the cold- and hot-water faucets.
- Loosen the sump by turning counterclockwise using the sump wrench that came with the filter. Careful! It will be full of water.
- Remove and dispose of used filter cartridge. (Cartridges may be recycled. Visit www.crystalquest.com/crystalquest_policies.htm under Preventive Routine Maintenance instructions.)
- Clean the inside of the sump with hot, soapy water. Rinse well. (Remember that you turned the water off at the sink you're working on.)
- Remove shrink wrap and insert the new filter cartridge in the sump. Cartridge must be installed according to the directional arrow on the cartridge which indicates "This End Towards Cap".
- Check O-ring(s). Lubricate with cooking oil if needed. Position O-ring(s) properly in the groove of the sump and tighten by turning it clockwise. Do not overtighten. Do not cross-thread at the sump or inlet/outlet ports. If cross-threaded, do not put or keep unit in service.
- Open the water valve slowly and fill the filter. Turn off the faucets and check the unit for leaks.
- Flush cartridge 3-4 times for 5 to 10 minutes to clear out media fines before using the water.




Fig 6